



## LINCOLN ELECTRIC K4405 Electrodes Low-Alloy Steel E8018-C1 H4R, 786WA4

Item **33VRH1405** Mfr. Model **ED030876**

### Product Details

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Item Reference: <b>786WA4</b>  | Width (in): <b>6</b>                    |
| Brand: <b>LINCOLN ELECTRIC</b> | Height (in): <b>14.75</b>               |
| Weight (lb): <b>50</b>         | Harmonization Code: <b>8311100000</b>   |
| Length (in): <b>6</b>          | Country of Origin: <b>United States</b> |

### Product Description

K4405 Stick Electrodes AWS Classification E8018-C1 H4R Material Low-Alloy Steel Process Stick Welding (SMAW) Overall Diameter 3/32 in Overall Length 14 in Tensile Strength (Minimum Required) 80 ksi Tensile Strength (As Welded) 82 to 89 ksi (Stress-Relieved 1 hr @ 1125 Degrees F) Yield Strength (Minimum Required) 67 ksi Yield Strength (As Welded) 67 to 76 ksi (Stress-Relieved 1 hr @ 1125 Degrees F) Series Excalibur 8018-C1 MR Weight 50 lb For Material Type Low-Alloy Steel to Low-Alloy Steel