



## HANNAY N818 Hose Reel with Hose

Item **22UCT73803** Mfr. Model **N818-25-26-10.5BH**

### Product Details

Brand: <b>HANNAY</b>	Length (in): <b>25.5</b>
Material: <b>Steel</b>	Width (in): <b>16.16</b>
Hose ID (IN): <b>1</b>	Harmonization Code: <b>9403200090</b>
Hose Length (ft): <b>50</b>	Country of Origin: <b>USA</b>
Weight (lb): <b>210</b>	

### Product Description

- Standard N series has a narrow frame and compact mounting base.
- Non-sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet: 90° balanced pressure swivel joint 1" female NPT threads.
- Standard outlet: 1" female NPT threads.
- Standard pressures to 2,000 psi (138 bar), available up to 6,000 psi (414 bar) – must specify.
- Temperatures from -40° F to +250° F (-40° C to +121° C).
- Consult mdi for other pressures and temperatures.
- 4-way roller assembly.
- SR and VR roller positions: swivel joint is standard on the right, TR roller positions: swivel joint is standard on the left.

Optional configurations are available, must specify,

### DIMENSIONS (inches)

Model

A  
B  
C  
D  
E  
F  
G  
H  
X  
Y

N818-25-26-10.5B

12  
6  
10.5  
12  
25.5

16.16  
26  
13.62  
10  
10