



## MKT FASTENING Drop-In Anchor Flange 3/8-16 PK25, 30PK32

Item **06QEZ0313** Mfr. Model **133800L**

### Product Details

|                               |                                       |
|-------------------------------|---------------------------------------|
| Item Reference: <b>30PK32</b> | Width (in): <b>6</b>                  |
| Brand: <b>MKT FASTENING</b>   | Height (in): <b>1</b>                 |
| Weight (lb): <b>1.65</b>      | Harmonization Code: <b>7316000000</b> |
| Length (in): <b>6</b>         | Country of Origin: <b>Taiwan</b>      |

### Product Description

Drop-In Anchor Anchor Diameter 1/2 in Overall Length 1 9/16 in Thread Size 3/8 In.-16 Thread Depth 0.5 in Thread Type Coarse Material Steel Finish Zinc Plated Flange Style Flanged Drill Bit Size 1/2 in Minimum Hole Depth 1 9/16 in Ultimate Shear Strength (4 000 psi Concrete) 3 714 lb Maximum Ultimate Shear Strength 3 714 lb Ultimate Tension Strength (4 000 psi Concrete) 4 824 lb Maximum Ultimate Tension Strength 4 824 lb System of Measurement Inch Bolt or Rod Size 3/8 in